

AMANA HEAT/COOL ROOM AIR CONDITIONERS

Electric Heat or Heat Pump Models

Complete room comfort with easy to use controls

Specifications for:

Electric Heat Models:

AE093A35MA

AE123A35MA


AE183A35MA

Heat Pump Models:

AH093A35MA

AH123A35MA

AH183A35MA



AE18 picture and control escutcheon not shown



AH18 Model

- **High Energy Efficiency** with models up to 10.0 EER saving you money when compared to other models.
- **Solid bottoms on outercases** for full seal - thru the wall installation.
- **100% Full Factory run test** on all units for high reliability and dependability. Units start the first time - every time!
- **Ball bearing fan motors** that are reliable, start quickly and run quietly.
- **Multi-directional airflow** to allow for cooling or heating to any part of the room. Some models contain automatic 2-way air swing feature.
- **Easy access slide out filter** (left or right side pullout) – has a permanent polypropylene filter mesh that is easy to remove and clean.
- **Hydrophilic coating on Evaporator and Condenser Coils** on ALL models which allows better moisture removal, increased air flow, increased heat exchange, higher efficiencies and longer compressor life.
- **Condensate drain spouts** on ALL models to direct condensate drainage.
- **LCDI power cords** improve safety and protect against crimping or cuts on power cords.

Amana
Heating & Air Conditioning

It's just what you'd expect
from an industry leader.

Electric Heat Models

Heat Pump Models

Amana Models

AE093A35MA


AE123A35MA

AE183A35MA

AH093A35MA

AH123A35MA

AH183A35MA

			DIGITAL CONTROL			DIGITAL CONTROL
General Features:						
Voltage	230/208	230/208	230/208	230/208	230/208	230/208
Discharge Air	Top	Top	Side	Top	Top	Side
Auto Air Swing	No	No	Yes	No	No	Yes
Slide-out Filter	Side Pull-out	Side Pull-out	Front Pull-out	Side Pull-out	Side Pull-out	Front Pull-out
Approx. Chassis Wgt.	94 lbs	99 lbs	137 lbs	98 lbs	103 lbs	150 lbs
Approx. Shipping Wgt.	110 lbs	115 lbs	145 lbs	114 lbs	119 lbs	170 lbs
Cooling:						
Capacity / BTUH	9,300 / 9,100	11,600 / 11,200	18,000 / 17,600	9,300 / 9,100	11,600 / 11,200	18,000 / 17,600
Amps	4.3 / 4.5	5.2 / 5.7	8.2 / 8.7	4.6 / 4.8	5.5 / 5.9	8.9 / 9.7
Watts	1,000 / 970	1,164 / 1,133	1,885 / 1,850	990 / 970	1,167 / 1,124	2,020 / 1,990
CFM	310	310	450	310	310	590
E.E.R.	10.0 / 10.0	10.0 / 10.0	9.7 / 9.7	10.0 / 10.0	9.5 / 9.5	9.0 / 9.0
Dehumidification - pts/hr	2.3	2.6	4.2	2.2	2.5	4.1
Electric Heat:						
Capacity / BTUH	10,700 / 8,500	10,700 / 8,500	11,000 / 8,600	10,700 / 8,500	10,700 / 8,500	11,000 / 8,600
Amps	14.8 / 13.4	14.8 / 13.4	15.4 / 13.9	14.8 / 13.4	14.8 / 13.4	15.4 / 13.9
Watts	3,416 / 2,792	3,416 / 2,792	3,555 / 2,898	3,416 / 2,792	3,416 / 2,792	3,555 / 2,898
Heat Pump: (Reverse cycle)						
Capacity / BTUH	n/a	n/a	n/a	8,400 / 8,100	10,300 / 10,000	16,000 / 15,700
Amps	n/a	n/a	n/a	4.0 / 4.2	5.0 / 5.3	8.0 / 8.7
Watts	n/a	n/a	n/a	920 / 900	1,140 / 1,100	1,840 / 1,790
C.O.P	n/a	n/a	n/a	2.8 / 2.8	2.7 / 2.7	2.7 / 2.7
Adjustable Change-Over Thermostat	n/a	n/a	n/a	Yes	Yes	Yes
Thermostatic Drain Valve	n/a	n/a	n/a	Yes	Yes	Yes
Dimensions:						
Outercase-sleeve						
Height	15 3/8"	15 3/8"	16 7/8"	15 3/8"	15 3/8"	16 7/8"
Width	22 5/8"	22 5/8"	26"	22 5/8"	22 5/8"	26"
Depth	24"	24"	27 3/4"	24"	24"	30 1/2"
Depth with Front	26 3/4"	26 3/4"	29 3/4"	26 3/4"	26 3/4"	32 1/2"

Features: (all models)

Electrical	6.0' LDCI power cord; Perpendicular plug; 20-amp circuit breaker
Agency Approval	U.L (Under Writers Laboratory) listed; USA and Canada
Chassis type	Slide-out for easy installation and service accessibility
Fan Speeds	2 speeds, High and Low
Fan ONLY	Yes – high speed
Condensate drain	Yes – condensate drain spout on the wall sleeve
Window kit	Yes – optional window mount kits are available



5-Year Parts & Labor Warranty:

1-Year entire unit and 5-Year sealed system components. Goodman will repair or replace any factory defective part or sealed system leak caused by a defective part and pay labor and associated services costs directly related to the part replacement or repair. See product warranty for complete details.


Plug Type

Perpendicular
20 Amps
250 Volts



Optional Accessories:

ACRK01A Sleeve adapter kit; converts old Amana® brand room air conditioner wall sleeves to accept AE093A35MA, AE123A35MA, AH093A35MA and AH123135MA room air conditioners.



Frank & Ron Hotel-Motel Supply, Inc.
888-854-6367
info@motelsupplies.com



It's just what you'd expect from an industry leader.